

EUROLAN Trunk cable MPO

Multimode OM4



Ordering information

Part number	Description
49L-40-2x12T-FA-xxx*	MPO-MPO Trunk 2x12xOM4 Female A
49L-40-24T-FA-xxx*	MPO-MPO Trunk 24xOM4 Female A
49L-40-12T-FA-xxx*	MPO-MPO Trunk 12xOM4 Female A

Ordering information

Part number	Description
49L-40-2x12T-FB-xxx*	MPO-MPO Trunk 2x12xOM4 Female B
49L-40-24T-FB-xxx*	MPO-MPO Trunk 24xOM4 Female B
49L-40-12T-FB-xxx*	MPO-MPO Trunk 12xOM4 Female B

* Available in lengths: 20,25,35,70,100m

Application

- Backbone connection in buildings and parks.
- Backbone in Data Centers.
- Backbone in industrial workshops.

Optical termination

Type	Multimode (PC/Flat polish) Package
Performance	Elite Low Loss
Maximum Insertion Loss	≤0,35dB
Return Loss	≥35dB
Operating Temperature	-40°C to +80°C
Test Wavelength	850nm or 1300nm
Durability (500 times)	≤0,1dB
Tensile strength	>15kg

- ✓ 100% pre-terminated and tested in factory to ensure the transfer performance
- ✓ Rapid configuration and network, reduce installation time.
- ✓ Support 40G and 100G network applications.
- ✓ Flammability: LSZH, OFNR, OFNP available.
- ✓ Support up to 12F, 24F, 48F, 72F, 96F, 144F, customized products are available.
- ✓ EIC 61754-7 and TIA 604-5-D